

MESSAGE NO: 9090112 MESSAGE DATE: 03/31/1999

MESSAGE STATUS: Active CATEGORY: Antidumping
TYPE: PRE-Preliminary PUBLIC ☒ NON-PUBLIC ☐
SUB-TYPE:

FR CITE: FR FR CITE DATE:

REFERENCE 9084113
MESSAGE #
(s):

CASE #(s): A-588-846

EFFECTIVE DATE: COURT CASE #:

PERIOD OF REVIEW: TO

PERIOD COVERED: 11/21/1998 TO

Notice of Lifting of Suspension Date:

TO: { Directors Of Field Operations, Port Directors }

FROM: { Director AD/CVD & Revenue Policy & Programs }

RE: NOTICE OF PRELIMINARY DETERMINATION IN AN ADD INVESTIGATION OF CERTAIN HOT-ROLLED FLAT-ROLLED CARBON- QUALITY STEEL PRODUCTS FROM JAPAN (A 588-846)

MESSAGE NO: 9090112

DATE: 03 31 1999

CATEGORY: ADA

TYPE: PRE

REFERENCE: 9084113

REFERENCE DATE: 03 25 1999

CASES: A - 588 - 846

- -

- - - -
- - - -

PERIOD COVERED: 11 21 1998 TO

LIQ SUSPENSION DATE:

TO: CMC DIRECTORS

PORT DIRECTORS

FROM: DIRECTOR, IMPORT OPERATIONS

RE: NOTICE OF PRELIMINARY DETERMINATION IN AN ADD
INVESTIGATION OF CERTAIN HOT-ROLLED FLAT-ROLLED CARBON-
QUALITY STEEL PRODUCTS FROM JAPAN (A 588-846)

RE: NOTICE OF A PRELIMINARY DETERMINATION IN AN ANTIDUMPING DUTY
INVESTIGATION OF CERTAIN HOT-ROLLED FLAT-ROLLED CARBON-
QUALITY STEEL PRODUCTS FROM JAPAN (A-588-846)

1. ON FEBRUARY 19, 1999, THE DEPARTMENT OF COMMERCE PUBLISHED
IN THE FEDERAL REGISTER ITS PRELIMINARY DETERMINATION OF
SALES AT LESS THAN FAIR VALUE IN THE ANTIDUMPING DUTY
INVESTIGATION OF CERTAIN HOT-ROLLED FLAT-ROLLED CARBON-

QUALITY STEEL PRODUCTS FORM JAPAN.

2. FOR PURPOSES OF THIS INVESTIGATION, THE PRODUCTS COVERED ARE CERTAIN HOT-ROLLED FLAT-ROLLED CARBON- QUALITY STEEL PRODUCTS OF A RECTANGULAR SHAPE, OF A WIDTH OF 0.5 INCH OR GREATER, NEITHER CLAD, PLATED, NOR COATED WITH METAL AND WHETHER OR NOT PAINTED, VARNISHED, OR COATED WITH PLASTICS OR OTHER NON-METALLIC SUBSTANCES, IN COILS (WHETHER OR NOT IN SUCCESSIVELY SUPERIMPOSED LAYERS) REGARDLESS OF THICKNESS, AND IN STRAIGHT LENGTHS, OF A THICKNESS LESS THAN 4.75 MM AND OF A WIDTH MEASURING AT LEAST 10 TIMES THE THICKNESS. UNIVERSAL MILL PLATE (I.E., FLAT-ROLLED PRODUCTS ROLLED ON FOUR FACES OR IN A CLOSED BOX PASS, OF A WIDTH EXCEEDING 150 MM BUT NOT EXCEEDING 1250 MM AND OF A THICKNESS OF NOT LESS THAN 4 MM, NOT IN COILS AND WITHOUT PATTERNS IN RELIEF) OF A THICKNESS NOT LESS THAN 4.0 MM IS NOT INCLUDED WITHIN THE SCOPE OF THESE INVESTIGATIONS. SPECIFICALLY INCLUDED IN THIS SCOPE ARE VACUUM DEGASSED, FULLY STABILIZED (COMMONLY REFERRED TO AS INTERSTITIAL-FREE ("IF")) STEELS, HIGH STRENGTH LOW ALLOY ("HSLA") STEELS, AND THE SUBSTRATE FOR MOTOR LAMINATION STEELS. IF STEELS ARE RECOGNIZED AS LOW CARBON STEELS WITH MICRO-ALLOYING LEVELS OF ELEMENTS SUCH AS TITANIUM AND/OR NIOBIUM ADDED TO STABILIZE CARBON AND NITROGEN ELEMENTS. HSLA STEELS ARE RECOGNIZED AS STEELS WITH MICRO-ALLOYING LEVELS OF ELEMENTS SUCH AS CHROMIUM, COPPER, NIOBIUM, TITANIUM, VANADIUM, AND MOLYBDENUM. THE SUBSTRATE FOR MOTOR LAMINATION STEELS CONTAINS MICRO-ALLOYING LEVELS OF ELEMENTS SUCH AS SILICON AND ALUMINUM.

STEEL PRODUCTS TO BE INCLUDED IN THE SCOPE OF THIS INVESTIGATION, REGARDLESS OF HTSUS DEFINITIONS, ARE PRODUCTS IN WHICH: 1) IRON PREDOMINATES, BY WEIGHT, OVER EACH OF THE OTHER CONTAINED ELEMENTS; 2) THE CARBON CONTENT IS 2 PERCENT OR LESS, BY WEIGHT; AND 3) NONE OF THE ELEMENTS LISTED BELOW EXCEEDS THE QUANTITY, BY WEIGHT, RESPECTIVELY INDICATED: 1.80 PERCENT OF MANGANESE, OR 1.50 PERCENT OF SILICON, OR

1.00 PERCENT OF COPPER, OR
0.50 PERCENT OF ALUMINUM, OR
1.25 PERCENT OF CHROMIUM, OR
0.30 PERCENT OF COBALT, OR
0.40 PERCENT OF LEAD, OR
1.25 PERCENT OF NICKEL, OR
0.30 PERCENT OF TUNGSTEN, OR
0.012 PERCENT OF BORON, OR
0.10 PERCENT OF MOLYBDENUM, OR
0.10 PERCENT OF NIOBIUM, OR
0.41 PERCENT OF TITANIUM, OR
0.15 PERCENT OF VANADIUM, OR
0.15 PERCENT OF ZIRCONIUM.

ALL PRODUCTS THAT MEET THE PHYSICAL AND CHEMICAL DESCRIPTION PROVIDED ABOVE ARE WITHIN THE SCOPE OF THIS INVESTIGATION UNLESS OTHERWISE EXCLUDED. THE FOLLOWING PRODUCTS, BY WAY OF EXAMPLE, ARE OUTSIDE AND/OR SPECIFICALLY EXCLUDED FROM THE SCOPE OF THIS INVESTIGATION:

ALLOY HOT-ROLLED STEEL PRODUCTS IN WHICH AT LEAST ONE OF THE CHEMICAL ELEMENTS EXCEEDS THOSE LISTED ABOVE (INCLUDING E.G., ASTM SPECIFICATIONS A543, A387, A514, A517, AND A506).

SAE/AISI GRADES OF SERIES 2300 AND HIGHER.

BALL BEARING STEELS, AS DEFINED IN THE HTSUS.

TOOL STEELS, AS DEFINED IN THE HTSUS.

SILICO-MANGANESE (AS DEFINED IN THE HTSUS) OR SILICON ELECTRICAL STEEL WITH A SILICON LEVEL EXCEEDING 1.50 PERCENT.

ASTM SPECIFICATIONS A710 AND A736.

USS ABRASION-RESISTANT STEELS (USS AR 400, USS AR 500).

HOT-ROLLED STEEL COIL WHICH MEETS THE FOLLOWING CHEMICAL, PHYSICAL AND MECHANICAL SPECIFICATIONS:

C 0.10 - 0.14%

MN 0.90% MAX

P 0.025% MAX

S 0.005% MAX

SI 0.30 - 0.50%

CR 0.50 - 0.70%

CU 0.20 - 0.40%

NI 0.20% MAX

WIDTH

44.80 INCHES MAXIMUM; THICKNESS

0.063 - 0.198

INCHES;

YIELD STRENGTH

50,000 KSI MINIMUM; TENSILE STRENGTH

70,000 - 88,000 PSI.

HOT-ROLLED STEEL COIL WHICH MEETS THE FOLLOWING
CHEMICAL, PHYSICAL AND MECHANICAL SPECIFICATIONS:

C 0.10 - 0.16%

MN 0.70 - 0.90%

P 0.025% MAX

S 0.006% MAX

SI 0.30 - 0.50%

CR 0.50 - 0.70%

CU 0.25% MAX

NI 0.20% MAX

MO 0.21% MAX

WIDTH

44.80 INCHES MAXIMUM; THICKNESS

0.350 INCHES

MAXIMUM;

YIELD STRENGTH

80,000 KSI MINIMUM; TENSILE STRENGTH

105,000 PSI AIM.

HOT-ROLLED STEEL COIL WHICH MEETS THE FOLLOWING
CHEMICAL, PHYSICAL AND MECHANICAL SPECIFICATIONS:

C 0.10 - 0.14%

MN 1.30 - 1.80%

P 0.025% MAX

S 0.005% MAX

SI 0.30 - 0.50%
CR 0.50 - 0.70%
CU 0.20 - 0.40%
NI 0.20% MAX
V(WT.) 0.10 MAX
CB 0.08% MAX

WIDTH

44.80 INCHES MAXIMUM; THICKNESS

0.350 INCHES

MAXIMUM;

YIELD STRENGTH

80,000 KSI MINIMUM; TENSILE STRENGTH

105,000 PSI AIM.

HOT-ROLLED STEEL COIL WHICH MEETS THE FOLLOWING
CHEMICAL, PHYSICAL AND MECHANICAL SPECIFICATIONS:

C 0.15% MAX
MN 1.40% MAX
P 0.025% MAX
S 0.010% MAX
SI 0.50% MAX
CR 1.00% MAX
CU 0.50% MAX
NI 0.20% MAX
NB 0.005% MIN
CA TREATED
AL 0.01 - 0.07%

WIDTH

39.37 INCHES; THICKNESS

0.181 INCHES MAXIMUM;

YIELD STRENGTH

70,000 PSI MINIMUM FOR THICKNESSES

0.148 INCHES AND 65,000 PSI MINIMUM FOR THICKNESSES

>0.148 INCHES; TENSILE STRENGTH

80,000 PSI MINIMUM.

HOT-ROLLED DUAL PHASE STEEL, PHASE-HARDENED, PRIMARILY

WITH A FERRITIC-MARTENSITIC MICROSTRUCTURE, CONTAINS 0.9 PERCENT UP TO AND INCLUDING 1.5 PERCENT SILICON BY WEIGHT, FURTHER CHARACTERIZED BY EITHER (I) TENSILE STRENGTH BETWEEN 540 N/MM AND 640 N/MM AND AN ELONGATION PERCENTAGE 26 PERCENT FOR THICKNESSES OF 2 MM AND ABOVE, OR (II) A TENSILE STRENGTH BETWEEN 590 N/MM AND 690 N/MM AND AN ELONGATION PERCENTAGE 25 PERCENT FOR THICKNESSES OF 2MM AND ABOVE.

HOT-ROLLED BEARING QUALITY STEEL, SAE GRADE 1050, IN COILS, WITH AN INCLUSION RATING OF 1.0 MAXIMUM PER ASTM E 45, METHOD A, WITH EXCELLENT SURFACE QUALITY AND CHEMISTRY RESTRICTIONS AS FOLLOWS: 0.012 PERCENT MAXIMUM PHOSPHORUS, 0.015 PERCENT MAXIMUM SULFUR, AND 0.20 PERCENT MAXIMUM RESIDUALS INCLUDING 0.15 PERCENT MAXIMUM CHROMIUM.

THE MERCHANDISE SUBJECT TO THESE INVESTIGATIONS IS CLASSIFIED IN THE HARMONIZED TARIFF SCHEDULE OF THE UNITED STATES ("HTSUS") AT SUBHEADINGS: 7208.10.15.00, 7208.10.30.00, 7208.10.60.00, 7208.25.30.00, 7208.25.60.00, 7208.26.00.30, 7208.26.00.60, 7208.27.00.30, 7208.27.00.60, 7208.36.00.30, 7208.36.00.60, 7208.37.00.30, 7208.37.00.60, 7208.38.00.15, 7208.38.00.30, 7208.38.00.90, 7208.39.00.15, 7208.39.00.30, 7208.39.00.90, 7208.40.60.30, 7208.40.60.60, 7208.53.00.00, 7208.54.00.00, 7208.90.00.00, 7210.70.30.00, 7210.90.90.00, 7211.14.00.30, 7211.14.00.90, 7211.19.15.00, 7211.19.20.00, 7211.19.30.00, 7211.19.45.00, 7211.19.60.00, 7211.19.75.30, 7211.19.75.60, 7211.19.75.90, 7212.40.10.00, 7212.40.50.00, 7212.50.00.00. CERTAIN HOT-ROLLED FLAT-ROLLED CARBON-QUALITY STEEL COVERED BY THIS INVESTIGATION, INCLUDING: VACUUM DEGASSED, FULLY STABILIZED; HIGH STRENGTH LOW ALLOY; AND THE SUBSTRATE FOR MOTOR LAMINATION STEEL MAY ALSO ENTER UNDER THE FOLLOWING TARIFF NUMBERS: 7225.11.00.00, 7225.19.00.00, 7225.30.30.50, 7225.30.70.00, 7225.40.70.00, 7225.99.00.90, 7226.11.10.00, 7226.11.90.30, 7226.11.90.60, 7226.19.10.00, 7226.19.90.00, 7226.91.50.00, 7226.91.70.00, 7226.91.80.00, AND 7226.99.00.00. ALTHOUGH

THE HTSUS SUBHEADINGS ARE PROVIDED FOR CONVENIENCE AND

CUSTOMS PURPOSES, THE WRITTEN DESCRIPTION OF THE MERCHANDISE UNDER INVESTIGATION IS DISPOSITIVE.

3. FOR IMPORTS OF CERTAIN HOT-ROLLED FLAT-ROLLED CARBON-QUALITY STEEL PRODUCTS FROM JAPAN, THE CUSTOMS SERVICE SHALL SUSPEND LIQUIDATIONS OF UNLIQUIDATED ENTRIES OF SUBJECT MERCHANDISE ENTERED OR WITHDRAWN FROM WAREHOUSE, FOR CONSUMPTION ON OR AFTER NOVEMBER 21, 1998, (90 DAYS PRIOR TO THE PRELIMINARY DETERMINATION, DUE TO THE DEPARTMENT'S PRELIMINARY DETERMINATION OF CRITICAL CIRCUMSTANCES). EFFECTIVE NOVEMBER 21, 1998, CUSTOMS SHALL REQUIRE, FOR SUCH ENTRIES, A CASH DEPOSIT OR BOND EQUAL TO THE MARGINS SHOWN BELOW:

MFR/PRODUCER/ EXPORTER	CUSTOMS ID NUMBER	MARGIN/ AD VALOREM PERCENTAGE
---------------------------	----------------------	-------------------------------------

NIPPON STEEL CORPORATION	A-588-846-003	25.14
NKK CORPORATION	A-588-846-001	30.63
KAWASAKI STEEL CORPORATION	A-588-846-002	67.59
ALL OTHERS	A-588-846-000	35.06

4. IF THERE ARE ANY QUESTIONS REGARDING THIS MATTER BY CUSTOMS OFFICERS, PLEASE CONTACT, VIA E-MAIL, THROUGH THE APPROPRIATE SUPERVISORY CHANNELS, OTHER GOVERNMENT AGENCY LIAISON, USING THE ATTRIBUTE "HQ OAB." THE IMPORTING PUBLIC AND OTHER INTERESTED PARTIES SHOULD CONTACT NITHYA NAGARAJAN, OFFICE OF AD/CVD ENFORCEMENT, IMPORT ADMINISTRATION, INTERNATIONAL TRADE ADMINISTRATION, U.S. DEPARTMENT OF COMMERCE, AT (202) 482-4243.
5. THERE ARE NO RESTRICTIONS ON THE RELEASE OF THIS INFORMATION.

PAUL SCHWARTZ

Company Details

*Party Indicator Value:

I = Importer, M = Manufacturer, E = Exporter, S = Sold To Party